

AUTO-TILT PRICING

Tilt Angle (degrees)	Cap. (lbs.)	Fork Width (inches)	Between Forks (inches)	Fork Length (inches)	Overall Fork Spacing (inches)	Overall Width (inches)	Overall Height (inches)	Tilt Time Empty (seconds)	Shipping Weight (lbs.)	Model No.
0-89	2000	7	13	42	27	35	36	:20	745	STR 89-20
0-89	4000	7	13	42	27	35	36	:20	745	STR 89-40
0-89	2000	7	13	42	27	60	36	:20	845	STR 89-20S
0-89	4000	7	13	42	27	60	36	:20	845	STR 89-40S

AUTO-TILT OPTIONS

Battery charger (ships loose)

AC Power, 115 Volt 3/4 hp Super Torque hydraulic power unit with pushbutton on 10' cord.

Air Power, internal air driven hydraulic power unit, requires 70 psi clean plant air, includes hand valve and lubricator.

Internal MEMA 4 washdown power unit and controls, prewired

BASE FRAME OPTIONS

Lag-Down, stationary mounting (wheels replaced with lag-down plates)

Special Paint Options: (Standard is AQ BLACK, (also available in AQ blue, brown and machine grey at no additional cost.)

Autoquip Safety Yellow or Orange chromates)

Epoxy paint to match Customer's Color (paint chip) with an Autoquip equivalent paint (2 part epoxy)

Steelcote "Stainless steel filled urethane primer and finish coating"(MCU type IV) for incidental food contact

Primer only. No additional charge.